

AQUEDUC 10

Industrial maintenance

Water/Cleaning and wash-down

MADE IN FRANCE AQUEDUC 10



Technical description:

Inner tube: SBR, black, smooth.

Reinforcement: 2 synthetic textile layers.

Cover: EPDM, brick red, fluted.

Temperature range: - 30 °C to + 70 °C.

Standard/Approval: NF - EN ISO 1403 type 2.

Complementary information:

Applications

Water discharge under pressure on industrial or urban sites and all high pressure water discharge applications in building and public works.

Advantages

- Flexible and easy to handle.
- Extremely resistant to atmospheric conditions due to the EPDM cover.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m
12.7 ± 0.6	3.20	19.1 ± 0.7	10	30	60	0.25	40
15.8 ± 0.7	3.35	22.5 ± 0.8	10	30	75	0.31	20 - 40
19.4 ± 0.7	3.55	26.5 ± 0.8	10	30	90	0.39	20 - 40
25.4 ± 1.0	3.85	33.1 ± 1.1	10	30	115	0.53	20 - 40

Branding:



TRELLEBORG

MADE IN FRANCE

AQUEDUC 10

Length in blue = stock item

Length in black = non stock

(see page 2 for minimum quantity of order)

CASCADE

Industrial maintenance

Water/Cleaning and wash-down

TRELLEBORG CASCADE



Technical description:

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, green, fluted.

Temperature range: - 30 °C to + 100 °C.

Standard/Approval: NF - EN ISO 1403.

Complementary information:

Applications

Water discharge under pressure on industrial or urban sites and all water discharge applications in building and public works.

Advantages

- Extremely resistant to ageing and atmospheric conditions.
- Very good resistance to high temperatures.
- Highly flexible and easy-to-hold due to the fluted cover.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m
12.7 ± 0.6	4.0	20.7 ± 0.7	10	32	70	0.28	40
15.8 ± 0.7	4.1	24.0 ± 0.8	10	32	80	0.34	20 - 40 - 80
19.4 ± 0.7	4.5	28.4 ± 0.8	10	32	120	0.45	20 - 40 - 80
25.4 ± 1.0	4.8	35.0 ± 1.1	10	32	150	0.60	20 - 40

Branding:



TRELLEBORG

CASCADE

Length in blue = stock item

Length in black = non stock

(see page 2 for minimum quantity of order)