WELDING & CUTTING HOSE (Oxygen & LPG)



Applications	For use with welding and allied processes in workshops, shipyards, construction sites and factories.
Tube	High ignition temperature synthetic rubber
Reinforcement	High tensile synthetic textile filament yarn
Cover	Excellent ozone and weather resistant synthetic rubber
Marking	ISO 3821 -2MPa (20 bar) -ID- NCR -YY

Blue (Oxygen)
Orange (LPG)

LPG hose
ISO 3821, AS 1335

Nominal ID		ID	OD	WP		BP		L	Product code
Inch	mm	mm	mm	bar	PSI	bar	PSI	m	
3/16	5	5.0	12.0	20	300	60	900	100	AXXL05OSJ01
1/4	6	6.3	13.3	20	300	60	900	100	AXXL06OSJ01
5/16	8	8.0	15.0	20	300	60	900	100	AXXL08OSJ01
3/8	10	10.0	17.0	20	300	60	900	100	AXXL10OSJ01

Oxygen & LPG hose
ISO 3821, AS 1335

Nominal ID		ID	OD	WP		BP		L	Product code
Inch	mm	mm	mm	bar	PSI	bar	PSI	m	
3/16+3/16	5+5	5.0+5.0	12.0+12.0	20	300	60	900	100	AXXT555SJ01
1/4+1/4	6+6	6.3+6.3	13.3+13.3	20	300	60	900	100	AXXT665SJ01
5/16+5/16	8+8	8.0+8.0	15.0+15.0	20	300	60	900	100	AXXT885SJ01
3/8+3/8	10+10	10.0+10.0	17.0+17.0	20	300	60	900	100	AXXT005SJ01

GAS HOSE (N_2, Ar, CO_2)

Applications	For use with welding and allied processes in workshops, shipyards, construction sites and factories.
Tube	High ignition temperature synthetic rubber
Reinforcement	High tensile synthetic textile filament yarn
Cover	Excellent ozone and weather resistant synthetic rubber
Marking	ISO 3821 -2MPa (20 bar) -ID- NCR -YY

ISO 3821



Nominal ID		ID	OD	WP		BP		L	Product code
Inch	mm	mm	mm	bar	PSI	bar	PSI	m	
3/16	5	5.0	12.0	20	300	60	900	100	AXXS05BSJ02
1/4	6	6.3	13.3	20	300	60	900	100	AXXS06BSJ02
5/16	8	8.0	15.0	20	300	60	900	100	AXXS08BSJ01
3/8	10	10.0	17.0	20	300	60	900	100	AXXS10BSJ01

NCR The Hose Specialist.