

# INTER GASOHOL HOSE



**NEWEST INNOVATION**

## Fuel / oil hose ( Gasohol E20/E85 )

**Application:** Most suitable for conveying gasoline with ethanol in combustion engine of all automotive lines and for general usage in contact with fuel/oil in manufacturing industries.

**Tube/Cover:** fuel/oil resistant synthetic rubber

**Working temperature:** -20 °C to +125 °C

**Safety factor:** 3 : 1

**Standard of compliance:** SAE J30 R7

**INTER** Environmental Friendly  
*Life Span Specialist*

**E20/E85  
GASOHOL**

\*Gasoline with Ethanol blended.

Nominal ID (Inch)	ID (mm)	OD (mm)	WP (kgf/cm <sup>2</sup> )	BP (kgf/cm <sup>2</sup> )	Length (m/roll)	Product Code
5/32	4	4.0	20	60	25	AZNU04BSZ01 *
3/16	5	5.0	20	60	25	AZNU05BSZ02 *
7/32	5.5	5.5	20	60	25	AZNU05BSZ04 *
1/4	6	6.3	20	60	25	AZNU06BSZ03
5/16	8	8.0	20	60	25	AZNU08BSZ03
3/8	9	9.5	20	60	25	AZNU09BSZ03
7/16	11	11.1	20	60	25	AZNU11BSZ02 *
1/2	12	12.7	20	60	25	AZNU12BSZ02 *
5/8	16	16.0	20	60	25	AZNU16BSZ03 *
3/4	19	19.0	20	60	25	AZNU19BSZ01 *
1	25	25.4	20	60	25	AZNU25BSZ01 *

“ \* ” Non - stock item



www.ncr-rubber.com

Quality is our key to the global market.

— **INTER** FUEL/OIL HOSE SAE J30 R7 1/4" WP 300 PSI BP 900 PSI GASOHOL E20/E85 —

