

RAIL & ROAD TANKER HOSE



Applications	For loading and unloading oil from tank truck.
Tube	Oil resistant synthetic rubber
Reinforcement	High tensile synthetic fabric with steel helical embedded wire
Cover	High abrasion, weather and oil resistant synthetic rubber
Marking	JNTR RT150 -- ROAD & RAIL TANKER HOSE -- BS 3492:1987 -- WP 150 PSI

BS 3492 : 1987



Nominal ID		ID	OD	WP		BP		L	Product code
Inch	mm	mm	mm	bar	PSI	bar	PSI	m	
1	25	25.4	36.6	10	150	30	450	40	BI-41001
1.1/4	32	31.8	43.6	10	150	30	450	40	BI-41002
1.3/8	35	34.9	48.2	10	150	30	450	40	BI-41003
1.1/2	38	38.1	51.2	10	150	30	450	40	BI-41004
1.3/4	44	44.5	58.2	10	150	30	450	40	BI-41005
2	51	50.8	65.2	10	150	30	450	40	BI-41006
2.1/2	63	63.5	77.6	10	150	30	450	40	BI-41007
3	76	76.2	91.0	10	150	30	450	40	BI-41008
4	102	101.6	120.0	10	150	30	450	40	BI-41009

OIL DELIVERY HOSE



Applications	For discharge of oil and some chemicals in refineries, factories and vessels.
Tube	Oil resistant synthetic rubber
Reinforcement	High tensile synthetic fabric
Cover	High abrasion and oil resistant synthetic rubber
Marking	JNTR OD150 -- OIL DELIVERY HOSE -- WP 150 PSI



Nominal ID		ID	OD	WP		BP		L	Product code
Inch	mm	mm	mm	bar	PSI	bar	PSI	m	
1	25	25.4	36.5	10	150	30	450	40	BL-42001
1.1/4	32	31.8	46.0	10	150	30	450	40	BL-42002
1.3/8	35	34.9	48.0	10	150	30	450	40	BL-42003
1.1/2	38	38.1	52.0	10	150	30	450	40	BL-42004
1.3/4	44	44.5	60.0	10	150	30	450	40	BL-42005
2	51	50.8	64.0	10	150	30	450	40	BL-42006
2.1/2	63	63.5	78.0	10	150	30	450	40	BL-42007
3	76	76.2	90.0	10	150	30	450	40	BL-42008
4	102	101.6	120.0	10	150	30	450	40	BL-42009